

NASA Goddard Space Flight Center, Greenbelt, Maryland 20771

ENGINEERING COLLOQUIUM

Monday, April 24, 2006 / 3:30 PM, Building 3 Auditorium

Jesse H. Ausubel

"Big Green Energy Machines" (talk version)

ABSTRACT -- *During the past 100 years motors have grown from 10 kilowatts to 1 million kilowatts, scaling up an incredible 100,000 times. During the 21st century, energy demand is likely to grow from the present 13 terawatts to 50 or even 100 terawatts, as chips go into 1000 objects per capita, or 10 trillion objects, and China, India, and other nations log into the game. Modestly compared to the 20th century, we may expect that the largest machines in the energy system will grow 5 to 10 times. I seek an energy system that is 5 to 10 times more powerful than the present system but fits within its present footprint. I will discuss two ideas for big green energy machines suiting the context of the 21st century. The first is the very potent Zero Emission Power Plant (ZEPP) operating on methane. The vision is a supercompact, superpowerful, superfast turbine putting out electricity plus CO₂ that can be sequestered. The second is the Continental SuperGrid to deliver electricity and hydrogen in an integrated energy pipeline.*

SPEAKER -- Jesse H. Ausubel is Director of the Program for the Human Environment at The Rockefeller University and concurrently a Program Director for the Alfred P. Sloan Foundation in New York City. Mr. Ausubel spent the first decade of his career in Washington DC working for the National Academy of Sciences and National Academy of Engineering. On behalf of the Academies, he was one of the main organizers of the first UN World Climate Conference in Geneva in 1979. He was also the main author of the 1983 report Changing Climate, the first comprehensive review of the greenhouse effect, and drafted Toward an International Geosphere-Biosphere Program: A Study of Global Change, the 1983 report originating the Global Change Program. In 1989 Mr. Ausubel moved to Rockefeller to establish a research program on long-term interactions of technology and the environment, patterns of technological diffusion, and means for a large prosperous society that spares nature. In 1991 he published the first paper referring to the "decarbonization" of the energy system. He co-authored several papers on technology and environment with the late Robert Herman (of microwave radiation fame).

Jesse H. Ausubel (Figure 1)

Director, Program for the Human Environment

The Rockefeller University

1230 York Avenue, New York NY 10021

<http://phe.rockefeller.edu>

ausubel@rockefeller.edu

Introduction

Imagine you are Robert Goddard, the year is 1926, and want to assemble a satellite that could be lofted on your new rocket. You visit the local electronics distributor in Worcester, Massachusetts, to obtain parts. You despair as soon as you grasp the weight and bulk of the components. Satellites were born and multiplied with transistors, integrated circuits, and other advances in microelectronics. The story of shrinking size and growing power and reach is completely familiar to engineers concerned with space flights. It is also my story today.

The World Wide Web is the most spectacular example we all now experience that, to become larger, systems must become smaller. The Web and Internet more generally are triumphs of scalability and economies of scale. If every computer still occupied the footprint of a mainframe computer of the 1960s, the Internet could never have succeeded. The miniaturization of every element of computer systems, from chips to video display, enabled the Internet to become pervasive and at the same time unintrusive. The elements also became cheaper. Think of the drop in price per calculation as semiconductor manufacturers introduced successively more powerful generations of chips and learned to fabricate each generation better. The shrinking of the elements of the system in cost, size, and intrusiveness enabled the system as a whole to multiply in power, features, and reach. To become larger in power, the system became smaller in size and cost.

During the past 100 years electric motors have grown from 10 kilowatts to 1 million kilowatts, scaling up an astonishing 100,000 times.

Yet, a power station today differs little in size from fifty or one hundred years ago. Regard the cathedral-like Bankside power station in London along the Thames opened in 1953 and converted in 2000 to serve as the modern gallery of the Tate Museum (**Figure 2**). The station, soaring 100 meters high and covering 3.5 hectares, provided at its peak a couple of hundred megawatts. A comparably powerful generator installed today, fueled by methane rather than heavy oil, might need 10 percent of the Bankside space. Alternately, the site could accommodate ten times the power. Fortunately, today a 2000 megawatt station need not cover 35 hectares, nor soar one thousand meters.

As with computer systems, scale matters to the electricity consumer as well as producer. Economist William Nordhaus observed a middle-class urban American household in 1800 would have spent perhaps 4 percent of its income on illumination: candles, lamps, oil, and matches. A middle-class urban American household today spends less than 1 percent of its income on illumination, and consumes more than 100 times as much artificial illumination as did its predecessor of two centuries ago. Happily, lamps do not occupy 100 times the space they occupied 200 years ago. Increases in luminous efficacy and decreases in cost of fuel allowed light to spread. (Improvements in safety counted too; lamps do not spark 100 times as many fires as formerly.)

Affordable electric power contributed as much as any technology to lifting human well-being in the 20th century. Mobility afforded by the internal combustion engine contributed hugely too. Electric power and mobility both depend on primary energy. During the 21st century, global primary energy demand is likely to grow from the present 13 terawatts to 50 or even 100 terawatts. One cause is chips going into 1000 objects per capita,

or 10 trillion objects, as China, India, and other nations log into the game. A second is that all people continue to seek to increase their range, thereby increasing their access to jobs, education, and enjoyment.

In fact, imagine simply that the rest of the world today lived like America. Satellite measurements of the kind GSFC engineers have pioneered have transformed the view from the airliner into global maps of upward light flux (Figure 3). How would the view from a plane circling the world at night brighten if everyone in the world lived like Americans? [The light intensity in the US ranges from 160 DN (or a radiance values of $2E-04$ watts/cm²/sr) per grid cell in New York City with population about 8 million to 0 in some areas of Alaska.ⁱ] Using population with 1-degree resolution for the year 1990, Figure 4 shows how bright the night around the world would become if everyone in the world emitted the watts per square centimeter per steradian of the median American in 1996.

Let's be more cautious, and not extrapolate the USA to the world but rather assume a big increase in efficiency gains and reduction in population growth. Still, a mere 1.5% per year growth of total energy demand during the 21st century, about two-thirds the rate since 1800, will multiply demand for primary energy three to four times between 2006 and 2100.

If size and power, of individual machines or the total system, grow in tandem, use of materials and land and other resources becomes unacceptably costly. Technologies succeed when economies of scale form part of their conditions of evolution. To be on the prudent side, I seek an energy system that is 5 to 10 times more powerful than the present system but fits within, or better, reduces its present footprint, a system of engines big in power and green in impact.

Modestly compared to the 20th century, we may expect that the largest machines in the energy system will also grow 5 to 10 times. Bigness is a plus for economizing on total use of materials as well as for controlling emissions because, although one big plant emits no more than many small plants, emission from one is easier to collect. Society cannot close the carbon cycle, for example, if we need to collect emissions from millions of microturbines. I will share with you two visions for big green energy machines suiting the context of the 21st century. The first is the very powerful Zero Emission Power Plant (ZEPP) burning methane. The second is the Continental SuperGrid to deliver electricity and hydrogen in an integrated energy pipe.

Very Powerful ZEPPs

The ZEPP, my first big green energy machine, is a supercompact, superfast, superpowerful turbine putting out electricity plus carbon dioxide that can conveniently be sequestered. Space engineers naturally think of rocket motors, and I expect many of the technical ideas for ZEPPs to come from rocketmen. A cruise missile engine and the furnace in your home's basement may compare in size but differ a bit in power. The challenge is to make a rocket engine that lasts, say, 300,000 hours.

A big difference with present thinking in the electric power industry is to choose methane rather than coal as the fuel. Investments by energy producers will make natural gas, methane basically, overtake coal globally as the lead fuel for making electricity over the next two to three decades. Methane tops the hydrocarbon fuels in heat value measured in joules per kilogram and thus lends itself to scaling up (**Figure 5**). Free of sulfur, mercury, and the other elements that contaminate coal (and oil), methane is

the best hydrocarbon feedstock. Although methane produces about half the carbon dioxide per unit of energy that coal does, it does still yield this greenhouse gas. Indeed, even in 2020 or 2030, we could need to dispose carbon from methane alone equal to half today's emission from all fuel and later methane might cause about 75% of total CO₂ emissions.

Is there enough methane? Space engineers and scientists have helped us to see seas of liquid methane on Saturn's moon Titan and affirm its universal abundance. In Earth, large amounts of methane have been found in hydrate form and at great depths. Experiments published in 2004 by Henry Scott of the University of Indiana showed methane formation from FeO, CaCO₃, and water by conditions in Earth's mantle. Thermodynamic guesses of methane formation in a reaction of Fayalite, CO₂, and water in Earth's crust even show the possibility of a self-sustained reaction. These several lines of evidence hint methane could feed ZEPPs for a very long time

So, prevention of climate change must focus on methane.

Can we find technology consistent with the evolution of the energy system to dispose economically and conveniently the carbon from making the kilowatts? The practical means to dispose the carbon from generating electricity consistent with the future context is the very large ZEPP. Let me try to leave ZEPPs indelibly in your minds.

The basic idea of the ZEPP is a gas power plant operating at very high temperatures and pressures, so we can bleed off the CO₂ as a liquid and sequester it underground in porous formations like those that harbor oil. We want to abandon the mess of post-combustion or even pre-combustion power plant CO₂ capture and move to direct stoichiometric combustion of methane and oxygen. **[Figure 6]**

A criterion for ZEPPs is working on a huge scale. Big total energy use means powerful individual ZEPPs because the size of generating plants grows even faster than use, though in spurts. Plants grow because large is cheap, if technology can cope. A famous engineering rule of thumb is that costs grow as the square root of size.

Analysis of the maximum size or power of power plants shows the maximum size grows in intense spurts. In the USA, one pulse, centered in 1929, quickly expanded power plants from a few tens of megawatts to about 340. [Figure 7] After a period in which plant size stagnated, a pulse centered in 1965 quadrupled maximum plant size to almost 1400 MW. The patterns for the world and a dozen other countries we have analyzed closely resemble the USA. For reference, my city, New York, now draws above 12,000 MW on a peak summer day.

The stagnation of maximum power plant size for the past three decades should not narcotize today's engineers. Growth of electricity use for the next 50 years can reasonably quadruple maximum plant size again. I project another spurt in plant size centered around the year 2020 to more than 5,000 MW.

Big ZEPPs means transmitting immense mechanical power from larger and larger generators through a large steel axle as fast as 3,000 revolutions per minute (RPM). The way around the limits of mechanical power transmission may be shrinking the machinery. Begin with a very high pressure CO₂ gas turbine where fuel burns with oxygen. Needed pressure ranges from 40 to 1000 atmospheres, where CO₂ would be recirculated as a liquid. The liquid combustion products would be bled out. **Figure 8** shows a simple configuration offered by colleagues from Tokyo Electric Power

with the six major components, combustor, turbine, regenerator, condenser, pump, and generator.

This scheme is a little rustic. We might let oxygen circulate and add methane when needed by local injection to make expansion almost isothermic. Dual cycles, maximum capacity, and changes in temperature in the regenerator with such dense gases all need to be considered by top engineers in laboratories to open a grand concourse of designs.

Fortunately for transmitting mechanical power, the high pressures shrink the machinery in a revolutionary way and so permit the turbine to rotate very fast. The generator could then also turn very fast, operating at high frequency, with appropriate power electronics to slow the generated electricity to 60 cycles.

Our envisioned hot temperature of 1500 degrees C will probably require using new ceramics now being engineered for aviation. Problems of stress corrosion and cracking will arise at the high temperatures and pressures and need to be solved. Even tiny amounts of impurities could cause big headaches as could by-products of the very high temperatures. Fizzy water might balloon into problems. Power electronics to slow the cycles of the alternating current also raises big questions. What we envision is beyond the state of the art, but power electronics is still young, meaning expensive and unreliable, and the art of the year 2020 and beyond may make our vision a reality.

The requisite oxygen for a 5000 MW ZEPP exceeds present capacity but could be made by cryoseparation. Moreover, the cryogenic plant may introduce a further benefit. Superconductors fit well with a cryogenic plant nearby. Superconducting generators are a sweet idea. Already today companies are selling small motors wound with high temperature

superconducting wire that halve the size and weight of a conventional motor built with copper coils and also halve the electrical losses.

Air Products has demonstrated in the laboratory a new approach to oxygen separation based on dense ceramic ion transport membranes (ITMs) which efficiently produce high-purity oxygen at high temperature

Colleagues at Tokyo Electric Power calculate the overall ZEPP plant efficiency could reach 70%, well above the 55% peak performance of gas turbines today (**Figure 9**).

The best programs to calculate thermodynamics of fuel/oxidant mixtures at high temperatures belong to rocket engineers. It would be good to reevaluate our expected efficiencies using such programs. In fact, our temperatures, reaching 1500 C are still not rocket heats, despite oxygen use.

With a ZEPP fueled by natural gas transmitting immense power at 60 cycles, the next step is sequestering the waste carbon. At the high pressure, the waste carbon is, of course, already liquid carbon dioxide and thus easily-handled. Opportunity for storing CO₂ will join access to customers and fuel in determining plant locations. Because most natural gas travels far through a few large pipelines, these pipelines are the logical sites for ZEPPs.

A logical place to sequester CO₂ emissions is in caverns underground, where coal, oil, and gas came from. The logic is encouraged by fact. On a small scale, CO₂ already profitably helps tertiary recovery of oil. In regions such as Texas, extensive systems pipe CO₂ for geologic storage in depleted oil fields for potential reuse in other nearby fields. In fact the past 20 years have proven the CO₂ storage industry. Commercial enterprises now store without leaks more than 30 million tons per year for enhanced oil recovery.

The challenge is large scale. The present annual volume of CO₂ from all sources is about 15 km³, about 500 times what oilmen now use. Of

course natural geological traps only occasionally contain hydrocarbons, so one can extend storage to the traps that lack oil and gas that prospectors routinely find. Grasping another opportunity, one could use aquifers in silicate beds to move the waste CO₂ to the silicates where “weathering” would turn it into carbonates and silica good for millions of years.

In short, the ZEPP vision is a supercompact, superpowerful, superfast turbine: 1-2 m diameter, potentially 10,000 MW or double the expected maximum demand, 30,000 RPMs, putting out electricity at 60 cycles plus CO₂ that can be sequestered. ZEPPs the size of a locomotive or even an automobile, attached to gas pipelines, might replace the fleet of carbon emitting antiquities now cluttering our landscape. As for mass and kit, pipes will come and go, but high pressures can narrow them, and siting the plants as adjuncts to existing natural gas pipelines minimizes need for more acreage. The acreage of a coal plant, including its rail yards and carbon heap, would easily accommodate a ZEPP producing 5-10 times the kilowatts including associated oxygen or other facilities.

In March 2005 the US company, Clean Energy Systems, Incorporated, achieved a milestone in energy engineering by putting in operation the world’s first methane ZEPP, at Kimberlina, near Bakersfield, California. Though only 5 MW, the operation combines gaseous oxygen (obtained from an on-site liquefier using stored liquid oxygen) and natural gas (supplied as on-site piped-in delivery from Southern California Gas sources) in a design that is the CES unique concept for high temperature steam production. Recycled water is the temperature modifier, and all are reacted at a near stoichiometric ratio so that only water and carbon dioxide are the products of the reaction. For the current operation the turbine exhaust is cooled, water

separation is made primarily by heat exchange with cooling water from an on site cooling tower, and the effluent CO₂ is released to atmosphere. The primary objective of the current test program is to demonstrate the extended reliability and low maintenance of the gas generator design, coupled with controlled performance capability, using oxygen, natural gas, and returned water, for direct application to a competitive commercial power plant. The location has an immediate possibility for a ZEPP concept demonstration with CO₂ sequestration since this site is located in an oil production region, with access to well heads within only miles of the facility.

A ZEPP of 40 MW in Norway is underway, and BP has announced a plan for Scotland.

I propose starting introduction of large ZEPPs in 2020, leading to a fleet of five hundred 5000 MW ZEPPs by 2050. This does not seem an impossible feat for a world that built today's worldwide fleet of some 443 nuclear power plants in about 30 years. ZEPPs, together with another generation of nuclear power plants in various configurations, can stop CO₂ increase in the atmosphere near 2050 AD in the range 450-500 ppm, about one-quarter more than today, without sacrificing energy consumption.

ZEPPs merit tens of billions in R&D, because the plants will form a profitable industry worth much more to those who can capture the expertise to design, build, and operate them. They offer the best chance for safe use of the immense wealth of hydrocarbons. Research on ZEPPs could occupy legions of researchers, working on development in conjunction with private companies. ZEPPs need champions. Let's whip the imaginations of electrical engineers to design and test power plants five times today's largest, chemical engineers to make more efficient processes suitable for plants two

orders of magnitude larger than present fertilizer plants, and geo-engineers to expand leak-proof CO₂ sequestration industries.

Like the jumbo jets that carry the majority of passenger kilometers, compact ultra-powerful ZEPPs could be the workhorses of the energy system in the middle of the next century. Yet, power companies could insert ZEPPs into densely settled regions such as eastern China without much change to the footprint of the energy system.

The Space Shuttle main engine, while its high-pressure pumps are smaller than what is envisioned for a ZEPP, operates in similar temperature and pressure regimes, namely ~490 atm and ~3,000 K at 37,000 rpm, and shows that our goals are achievable.

The Continental SuperGrid

Here let me introduce a second, even bigger green energy machine, the **Continental SuperGrid** to deliver the preferred energy carriers, electricity and hydrogen, in an integrated energy pipeline. The fundamental design is to wrap superconducting cable around a pipe pumping liquid hydrogen that provides the cold needed to maintain superconductivity (**Figure 10**). The SuperGrid is doubly super: first because it is the apex, and second because it employs superconductivity. The SuperGrid would not only transmit electricity but also store and distribute the bulk of the hydrogen ultimately used in fuel cell vehicles and generators or in refreshed internal combustion engines.

While methane is a good energy carrier, environmentally hydrogen is better. Its combustion yields only water vapor and energy. In the 1970s journalists called hydrogen the Tomorrow Fuel, and critics have worried that hydrogen will remain forever on the horizon, like fusion. For

hydrogen tomorrow is now today. Long popular as rocket fuel and in other top performance market niches, hydrogen is a thriving young industry. Price is coming down as experience rises (**Figure 11**) Visit the Dow facility in Freeport, Texas, to see hydrogen operations at the scale of hundreds of megawatts. World commercial production in 2003 exceeded 40 billion standard cubic feet per day, equal to 75,000 MW if converted to electricity, and USA production, which is about 1/3 of the world, more than tripled between 1990 and 2000 (**Figure 12**), and the long term trend is clearly upward. Over 16,000 kilometers of pipeline transport hydrogen gas for big users, with pipes at 100 atmospheres as long as 400 kilometers from Antwerp to Normandy. But the scale I have in mind is orders of magnitude larger.

By continental, I mean coast-to-coast, for example, across the 4,000 kilometers of North America, making one market not only for hydrogen but also for electricity. Superconductivity solves the problem of power line losses, and the continental scale makes the electric power system much more efficient by flattening the electricity load curve which still follows the sun. By high capacity, I mean 40,000-80,000 MW. The cable [**Figure 13**] needs the capacity to accept the power of a 10 GW plant, for which ZEPPs set the precedent, and would carry direct current and might look either like a spine or a ring. In fact topology is a key research question. Power converters would connect the direct current SuperGrid at various points to existing, high-voltage alternating current transmission substations. Continental SuperGrids should thrive on all continents. A continental system might cost about \$1 trillion, or \$10 billion per year for 100 years

In its early realization some forty 100-km long sections of the grid might be joined by nuclear plants of several thousand MW supplying to the

SuperGrid both electricity and hydrogen. Present hydrogen comes from cooking hydrocarbons, about 85% from steam reforming of methane and the rest from oil residues or coal gasification. To spare the chores and costs of carbon capture and sequestration, hydrogen, of course, must eventually come from splitting water, and the energy to make the hydrogen must also be carbon-free. According to the historical trend of decarbonization, large-scale production of carbon-free hydrogen should begin about the year 2020.

Nuclear power fits with the SuperGrid because of its low cost of fuel per kilowatt hour and its operational reliability at a constant power level. High-temperature reactors with coated-particle or graphite-matrix fuels promise a particularly efficient and scalable route to combined power and hydrogen production. **[Figure 14]** The Chinese company, Huaneng Power, is now building the world's first commercial pebble bed reactor, 200MW, in Shandong Province in crowded eastern China. Thermochemically, high-temperature nuclear plants could nightly make H₂ on the scale needed to meet the demand of billions of consumers. Nuclear energy is inherently 10,000 or even 100,000 times as compact as hydrocarbons (**Figure 15**) and thus scalable. Like ZEPPs, high temperature reactors could be 5,000 to 10,000 megawatts. Thus, the acreage for power parks and even the number of plants need differ little from today. In many regions and countries the future energy system can fit within the footprint of the present energy system.

Operating 24 hours per day, the plants would double the basic efficiency of the capital stock of the electric power industry, which is geared to peak demand, about twice the level of baseload but unused half the time. The latent hydrogen storage capacity of the SuperGrid, combined with fuel cells or other new engines, may allow electricity networks to shift to a

delivery system more like oil and gas, away from the present, costly, instant matching of supply to demand. [Figure 16]

Technical choices and challenges abound, about cryogenics and vacuums, about dielectric materials under simultaneous stress from low temperature and high fields, about power control and cable design. Engineers need to improve Supercable design and demonstrate performance of high temperature superconducting wire at commercial electrical current levels. In fact, *Science* magazine 31 March (p. 1911) reported signal progress by Kang of ORNL and colleagues on high-performance superconducting wires: short segments of a superconducting wire that meets or exceeds performance requirements for many large-scale applications of superconduct, especially those requiring a high current YBCO film.

The next step, achievable over 2-3 years, might be a flexible 100 meter Supercable, 10 centimeters overall diameter, 5000 volts, 2000 amperes, 10 MW direct current, with a 3 centimeter diameter pipe for 1 meter per second H₂ flow, using magnesium diboride or other wire demonstrating constant current under variable load and low ripple factor.

Looking forward, joints and splices are tough problems, emblematic of the general problem of making parts into a system that works, a problem that challenges engineers to their greatest achievements.

For ultimate safety, security, and aesthetics, let's put the SuperGrid, including its cables and power plants, underground. The decision to build underground critically determines the cost of the SuperGrid. But, benefits include reduced vulnerability to attack by human or other nature, fewer right-of-way disputes, reduced surface congestion, and real and perceived reduced exposure to real or hypothetical accidents and fallout. Since 1958 Russia has operated underground nuclear reactors near Zheleznogorsk in

Central Siberia. The SuperGrid multiplies the chances to site reactors that produce hydrogen far from population concentrations and pipe their products to consumers.

The USA has about 8000 large generators. Suppose the fleet dropped in half because of the success of ZEPPs and other larger machines even as demand rises. If the generators are networked in a smart mesh that moves electric power around at a continental scale, saboteurs (or earthquakes) would probably need to remove 40 or more plants (10% of supply) to make a big problem. Not so easy. Think of the Supergrid concept as an “eBay” for power, in which everyone can buy and sell, no matter where you are, with transaction costs very low. Idaho could be the Saudi Arabia of hydrogen, shipping to all corners of North America. Creating this mesh with very low cost for transport, and putting it underground, should lift security

An even more evolved concept for the underground corridors combines energy with transport. Sharing the tunnels, magnetically levitated trains in low pressure tubes would run on linear motors of superconducting magnets, speeding from one edge of a continent to another in 1 hour (**Figure 17**). By the way, China confirmed its leadership in new transport technology with an announcement 13 March 2006 that it will build the world’s 2nd commercial maglev between Shanghai and Hangzhou, 175 km apart.

I am now looking ahead 100 years, but that is a good time frame for major infrastructure systems. Let's recall that 103 years ago the Wright Brothers launched the first successful airplane with a 12 horsepower engine for 59 seconds. The maglevs could spread the infrastructure cost over multiple uses.

Magic words for the SuperGrid are hydrogen, superconductivity, zero emissions, and small ecological footprint, to which we add high temperature reactors, energy storage, security, reliability, and scalability. The long road to the continental SuperGrid begins with the first 10 to 20 km segment addressing an actual transmission bottleneck. The prize is that the SuperGrid pipe can carry ten or more times the power of a cable today within the same diameter. In fact, the diameter of the supercable need be only a 1/2 meter or so. **[Figure 18]**

Conclusion

Small is indeed beautiful, when small also means powerful and cheap, like the machinery of the Internet. The energy system requires economical green ideas that are comparably big in power yet small in impact.

Solar and the so-called renewables are not green when considered on the large scales required. In round numbers a single 1,000 MWe nuclear plant equates to prime farmland of more than 2500 square kilometers producing biomass, to a wind farm occupying 750 square kilometers, or a PV plant of about 150 square kilometers plus land for storage and retrieval. **[Figure 19]** On large scales, we are stuck with about 0.4 watts per hectare from biomass, 1.2 watts per square meter from wind, and 5-6 watts per square meter from light. While a present natural-gas combined cycle plant uses about 3 metric tons of steel and 27 cubic meters of concrete per average megawatt electric, a typical wind-energy system uses a horrifying 460 metric tons of steel and 870 cubic meters of concrete. Solar and renewables in every form require large and complex machinery to produce many megawatts. **[Figure 20]** Inherently, they lack efficiencies and economies of scale. Like fixed low-yield agriculture, to produce more calories or

kilowatts solar and renewables simply multiply in extent, linearly. Unlike the Internet, solar and renewables cannot become much smaller as they become much larger. Thus, they will grow little.

Fortunately, the enabling technologies of the new millennium such as high temperature ceramics and superconductors make possible big green energy machines such as ZEPPs and Continental SuperGrids (**Figure 21**). ZEPPs and SuperGrids can multiply the power of the system by 5 or 10 times while also shrinking it in a revolutionary way. Engineers like Robert Goddard will bring these machines to beautiful fruition.

ⁱ The radiance values were calculated according to the formula: Radiance = $DN^{(3/2)} * 10^{(-10)}$ watts/cm²/sr, where DN is a digital number (grid cell value). Sr abbreviates Steradian, the standard unit of a solid angle which determines the surface area on a sphere.